

# Titan® MR 5400 MyRIDE, Model No. 75317TA



## TECHNICAL SPECIFICATIONS AND FEATURES

<b>Engine</b>	Kawasaki FR730V_S09-R, 17.9 kW (24.5 hp), 726 cc, overhead valve, V-twin (cast iron sleeves) single camshaft, air cooled engine with full pressure lubrication and full flow oil filter. Air cleaner is standard style with single paper filter element. High idle speed set at 3,600 +/- 100 rpm.
<b>Construction</b>	Riveted 10 gauge steel.
<b>Deck Size</b>	137.2 cm (54.0 inch).
<b>Deck Configuration</b>	Right side discharge, mid mounted rotary. Fabricated grade 50, 10 gauge steel deck with welded reinforcements, mounting brackets and gauge wheel brackets. Frame supported. Left, centre and right front mounted anti-scalp rollers with four height positions.
<b>Deck Spindles</b>	Die cast 19.7 cm (7.8 inch) aluminum spindle housing (3). Permanently lubricated precision ball bearings. 2.54 mm (1.0 inch) diameter spindle shaft.
<b>Height of Cut</b>	3.9 cm to 11.4 cm (1.5 to 4.5 inches), adjusts in 6.0 mm (0.25 inch) increments.
<b>Hydro Drive Unit</b>	Dual Hydro-gear ZT-2800 transaxles with charge pumps and oil filters. Belt drive with self-tensioning system.
<b>Ground Speed</b>	<b>Forward:</b> 0 to 13.7 km/h (0 to 8.5 mph). <b>Reverse:</b> 0 to 6.9 km/h (0 to 4.3 mph).
<b>Wheel Base</b>	126.2 cm (49.7 inches) – centre of rear tyre to centre of front tyre.
<b>Steering Control</b>	Ergonomic, adjustable steering levers with heavy-duty dampeners.
<b>Width</b>	177.8 cm (70.0 inches) – deflector down.
<b>Minimum Gate Width</b>	154.9 cm (61.0 inches) – deflector up.
<b>Overall Length</b>	205.7 cm (81.0 inches).
<b>Overall Height</b>	121.9 cm (48.0 inches) – to top of seat.
<b>Tyres</b>	<b>Front:</b> 13 x 6.5-6 inch, 4 ply, smooth tread, pneumatic. <b>Rear:</b> 22 x 11.0-10 inch, 4 ply, turf tech tread, pneumatic.
<b>Fuel Tank Capacity</b>	18.9 litres (single mid mounted tank).
<b>Weight</b>	362.9 kg (800.0 lbs.).
<b>Seat</b>	45.7 cm (18 inch) handcrafted high back with pivoting armrests. Seat pan fastened to MyRIDE suspension platform.
<b>Suspension</b>	MyRIDE suspension system incorporating three coil over shock absorber assemblies (rear two adjustable, front fixed) allowing 7.6 cm (3.0 inches) of travel.
<b>Warranty</b>	<b>Consumer:</b> <u>Machine</u> 3 years, <u>Engine</u> 3 years, <u>Wear Parts</u> (belts, blades, tyres etc.) 90 days, <u>Battery</u> 1 year (first 90 days parts and labour, balance of year (91-365 days) parts only). <b>Commercial:</b> <u>Machine &amp; Transaxles</u> 3 years / 300 hours (whichever occurs first), <u>Engine</u> 3 years, <u>Wear Parts</u> 90 days, <u>Battery</u> 1 year (first 90 days parts and labour, balance of year (91-365 days) parts only). <b>Attachments:</b> 1 year. <b>NOTE:</b> Engine warranty is through Kawasaki US, but administered by Toro Australia. <i>For all other conditions, refer to the online The Toro Warranty statement.</i>

Any specifications and dimensions in this Specs & Spares release are subject to change without notice and without incurring any obligation.

**For additional technical and servicing information regarding this mower, refer to Service Bulletin TSB01/21, Issued April 1, 2021.**

**PLEASE NOTE:** The Toro Part Numbers quoted are correct at the time of this Specs & Spares release. Always refer to the appropriate Parts Manual based upon the machine's serial number to ensure correct parts availability and fitment.

### ACCESSORIES AND ATTACHMENTS

Product	Part No.
Toro Product Cover	137-7012
Powered Twin Bagger Kit*	79346
Heavy Duty Bagger Cover Kit	140-5036
Blowout Ring Kit	140-5122
Deck Lift Assist Kit	140-5123
Bucket – 5 US Gallon	133-2533
Bucket Mount Kit	140-2066
Deck Maintenance Jack #	127-6666
Jack Mount Kit	140-2067

# Jack requires mount kit 140-2067.

Product	Part No.
Attachment Mount Kit	140-5125
MyRIDE Heavy Duty Shock & Spring Kit	140-2069
Light Kit	136-7493
Recycler Kit	136-7489
ROPS Kit	139-2638
Striping Kit	140-5120
Weight Kit	140-5084
Sunshade	137-7011

\*Bagger Kit includes blower, attachment mount and weight kits.

### REGULAR MAINTANENCE ITEMS

Product	Part No.
A/C Paper Element	11013-0752
A/C Foam Element (optional)	11013-7046
Engine Oil Filter	49065-0721
Engine Fuel Filter	49019-0031
Spark Plugs	NGK® BPR4ES
Rocker Cover Gasket (2 required)	11061-7083
Transaxle Oil Filter (2 required)	109-3321

Product	Type / Capacity
Engine Oil Type	Detergent engine oil, API service SF, SG, SH, SJ or SL. Engine Oil SAE-30 or 10W-40 for normal conditions – otherwise refer to Operator's Manual.
Engine Oil Capacity	Without oil filter change – 1.8 litres With oil filter change – 2.1 litres
Transaxle Oil	Toro HYPR-OIL 500 Hydraulic Fluid
Transaxle Oil Capacity	Approximately 4.45 litres required for complete system change including filters replaced.

Product	Part No.	Product	Part No.
Traction Drive Assembly Drive Belt	133-4371	Deck Belt Tensioner Arm Spring	138-7228
Traction Drive Assembly Flat Idler Pulley	138-7597	Deck Anti-Scalp Roller	1-603299
Traction Drive Assembly Idler Pulley	119-8822	Blade Attaching Screw	51-4060
Traction Drive Assembly Engine Pulley	138-9831	Blade Attaching Screw Washer	125-1736
Transaxle Pulley and Fan Kit	135-7343	Fuel Tank Cap	137-4119
PTO Clutch	127-3410	Caster Wheel Tyre	126-5959
Deck Spindle Housing	139-2357	Rear Tyre	139-7536
Deck Spindle Drive Belt	133-7076	Ignition Key	63-8360
Deck Spindle Pulley	139-7455	Throttle Cable	139-5808
Deck Spindle Drive Belt Flat Idler Pulley	132-4718	Choke Cable	139-2402
Deck Spindle Shaft	115-2642	Belt Cover – RH	133-9283
Deck Spindle Bearing (2 required)	116-0720	Belt Cover – LH	133-9282
Deck Plastic Discharge Deflector	117-1270	Battery (Dry)	104-8162

### Blade Types

Blade Type	Part No.
Standard - (Bagger/Hi-Lift)	115-9650-03
Optional - (Recycler/Mulch)	115-4999-03